

1		15.6	1. 15.6inch 2. 1920 x 1080 16:9 3. IPS 4. 1000:1 5. 220cd/m2 6. 30ms
2		15.6	1. 2. 5080LPI 3. 8192 4. ±0.5mm Center ±3mm Corner 5. 10 mm 6. 260 PPS 7. 8. 10
3			1. EPP , 16 10 0 9 6 2. 3. 3DES DES MAC ANSI X9.8PIN Block ANSI X9.24 SM2 SM3 4. 5.
4			1. ≤ 0.0001% 2. <1S() 1 1 1:N 3. 256 4. 1,000,000 100 5. / / 6. 7.
5			1. 300*300dpi 2. / 3. 50mm/sec 54mm 87mm 4. 0.75~1.1mm 5. BMP JPEG :150dpi 200dpi 300dpi

			6. RS232/USB 7. 8. ISO/IEC14443TYPEB 9. ≤ 3 10. GA450-2003 1GA4502003< > 1 GA467-2004 GA490-2004 11.
6			1. 2. IC RFID [] 3. IBM ISO ANSI DIN ISO/ANSI ISO7810/12/13 4. 5. SM4 [IC] 6. ISO7816-1 2 3 4 7. PBOC 8. EMV2000 9.
7			1. 2. 3. 4. 5. IC IC 6. ISO/IEC 14443 Type A Type B 7. PBOC 8. EMV2000
8			1 80mm -1mm 2 3 RS232/USB 4 100mm/s 5 100mm 6 7 8 9 120 10 20 11